

## Calcium Acetate Pharma

SPECIFICATIONS	CONTROL LIMITS
Appearance	white powder or agglomerate
Assay on dried matter	99.0 – 100.5 %(m)
Water	7.0 %(m) max.
pH of 5% solution	7.2 – 8.2
Identification Ca and Acetate	conform test
Aluminium (Al)	1 ppm max.
Arsenic (As)	3 ppm max.
Barium (Ba)	50 ppm max.
Heavy metals (as Pb)	10 ppm max.
Magnesium (Mg)	500 ppm max.
Potassium (K)	500 ppm max.
Sodium (Na)	500 ppm max.
Chloride (Cl)	330 ppm max.
Nitrate (NO <sub>3</sub> )	conform test
Sulphate (SO <sub>4</sub> )	600 ppm max.
Readily oxidizable substances	conform test
Fluoride (F)	50 ppm max.
Lead (Pb)	10 ppm max.
Strontium (Sr)	500 ppm max.
Residual Solvents	conform test
Iron (Fe)	20 ppm max.
Solubility	conform test

Pharmaceutical grade conforms to the latest USP and EP.

Analytical methods available on request.

For more detailed information please see Technical Data Sheet and Safety Data Sheet.

**Warranty.** This information herein is offered as a guide and is believed to be accurate and reliable as of the date of the printing. The values given are not to be considered as a warranty and they are subject to change without prior notice. For additional information regarding our products or for information concerning current specifications, please contact our Technical Service.